

SPECIFICATION HIGHLIGHTS

H3-45 VIP

USA: 1-800-621-5519

California - Bay Area
Tel: (951) 360-2650

California - Southern
Tel: 1-800-421-9958

Florida - Jacksonville
Tel: 1-800-874-7740

Illinois - Chicago
Tel: (847) 778-7475

New Jersey - South Plainfield
Tel: 1-800-223-0830

Tennessee - Nashville
Tel: 1-877-299-8881

Texas - Fort Worth
Tel: 1-866-773-8678

Texas - Houston
Tel: 1-877-602-0273

Canada: 418-883-3306

Alberta - Calgary
Tel: 1-403-519-3477

Alberta - Ft McMurray
Tel: 1-780-713-0274

British Columbia - Richmond
Tel: 1-604-940-3306

Ontario - Mississauga
Tel: 1-905-738-0881

Quebec - Lévis
Tel: 1-866-870-2046

Quebec - Montreal
Tel: 1-866-870-2046

prevostcar.com

    @PrevostCoach
@PrevostPromos

These specifications are based on the latest product information available at time of printing (11/15) and are subject to change. Contact your Prevost Sales Manager for full details on standard features, packages and options available on the latest model.

* Prevost, The Ultimate Class and H3-45 VIP are registered trademarks of Prevost, a division of Volvo Group Canada Inc. All rights reserved.

GENERAL

Length, Overall (ft)	45
Wheelbase (in)	316.12
Width, Overall (in)	102
Height, Overall (in)	149
Floor-to-ceiling Height (in)	83
Cabin Floor Height (in)	63
Underfloor Storage (w/Driver A/C) (cu. ft.)	497
Underfloor Compartment Doors Width (in)	48.5
Entrance Door Width (in)	27
Ground Clearance (in)	11
Overhang (incl. Bumper) - Front (in)	75
Overhang (incl. Bumper) - Rear (in)	107
Turning Radius (ft)	42
Body Construction (Structure)	Integral Stainless Steel

Body Construction (Outer Shell - up to window level)	Fiber Composite
Body Construction (Sub-Frame)	Low-Alloy/High Tensile Steel

State-of-the-art Soundproofing	Standard
Fuel Tank (US Gallons)	222
Fuel Filler Necks on Both Sides	Standard
Gross Vehicle Weight Rating (lb)	55,500
Axle Design Load Capacity - Front (lb)	19,000
Axle Design Load Capacity - Drive (lb)	22,500
Axle Design Load Capacity - Tag (lb)	14,000
Wet Weight, w/Driver A/C (lb/kg)	31,140 / 14,125
Wet Weight, w/Full A/C (lb/kg)	31,840 / 14,442
Driver-only A/C	Standard
Full A/C	Optional
A/C Condenser with Copper Fins	Standard with full A/C
A/C Refrigerant	134A
Cooling Capacity/Full A/C	108,000 btu/hr
Two-Year Warranty	Standard
Five-Year Warranty (Engine & Transmission)	Standard

TIRES AND WHEELS

Michelin 315/80R22.5 (Drive Axle)	Standard
Michelin 365/70R22.5 (Front and Tag Axles)	Standard
Polished Aluminum Wheels 22.5 x 9 in. (Drive Axle)	Standard
Polished Aluminum Wheels 22.5 x 10.5 in. (Front and Tag Axles)	Standard
Dura-Bright Coating (Aluminum Wheels)	Optional
Michelin 455/55R22.5 Super Single Tires with 14 in Wheels (Drive Axle)	Optional

POWERTRAIN

EPA compliant Volvo D13 engine 500HP with Diesel particulate Filter (DPF) and Selective Catalytic Converter (SCR)	Standard
Engine Torque Rating (ft.-lb.)	1750
Allison 5th Generation 6 speed Automatic transmission B500 (Commercial) / 4000MH (RV)	Standard
Allison Hydraulic Transmission Retarder	Optional
Cruise Control	Standard
Engine Brake (on all cylinders)	Optional
Pneumatic Drive Belts Tensioners	Standard
Turbo-boost Gauge	Standard
3-Speed Engine Cooling Fan	Standard
Two-step Dual Filter with water separator	Standard
Prevost Liaison, 1 year coverage	Standard
Engine maintenance software with laptop	Optional

BRAKES

All-disc Brakes with ABS	Standard
Front Wheels Brake Boosters	Type 27
Driver Wheels Brake Boosters	Type 24-24
Tag Wheels Brake Boosters	Type 14-16
Parking Brake Booster on Tag Wheels	Standard

STEERING AND SUSPENSION

Tilt and Telescopic Steering Wheel	Standard
ZF Variable Assistance Power Steering System	Standard
Independent Suspension System	Standard
Front and Drive Axle Sway Bars	Standard
Integrated Pneumatic Level - Low Leveling System	Standard
Liftable Tag Axle	Standard

ELECTRICAL SYSTEM

4 AGM batteries	Standard
Prime - battery management system	Standard
Fully Multiplexed Electrical System	Standard
12-volt Exterior Lighting	Standard
24-volt Main System	Standard
Additional Alternator Configurations for conversion	Optional

INNOVATIVE SAFETY FEATURES

Prevost Electronic Stability Program	Standard
Prevost Aware - Adaptive Cruise Braking System	Optional
Automatic Fire Suppression System for Engine Compartment	Standard
BFI Tire Pressure Monitoring System	Standard
Xenon Low Beam Headlights	Standard

FACTORY-INSTALLED EQUIPMENT

Factory Slide-Outs (Electric Motors & Pneumatic Seals)	Optional
(1, 2, 3 or 4 Slide-outs Available)	
Front Slide Driver's Side (Interior Dimensions)	170" x 30" x 71"
Rear Slide Driver's Side (Interior Dimensions)	86" x 24" x 60"
Rear Super Slide Driver's Side (Interior Dimensions)	126" x 24" x 60"
Front Slide Passenger Side - Flush Floor (Interior Dimensions)	148" x 24" x 71"
Rear Slide Passenger Side (Interior Dimensions)	86" x 18" x 71"
Rear Super Slide Passenger Side (Interior Dimensions)	126" x 18" x 71"
Choice of Side Window Arrangement & Type (Fixed, Electrical Awning or Sliding)	Optional
Fog Lights	Standard
Driver's Window Blind	Optional
Electric Windshield Blinds LH and RH	Optional
Ramco Remote Heated Rearview Mirrors	
w/ Separate Convex Top (Painted in Black)	Standard
w/ Separate Convex Top (Chromed)	Optional
Signal Mirrors w/ LED Light	Optional
Central Electrical Door Locking System	Standard
Remote or keyless unlatch of the entrance door	Standard
Keyless keypad w/ multi-code capability	Standard
Remote Keyless Locking (Entrance Door)	Standard
Remote Keyless Locking (Compartment Doors)	Standard
Trailer Hitch Package (20,000 lb)	Standard
Trailer Air Brake Connection	Optional
Cornering and Docking Lights	Standard
Courtesy Lights Blinker Switch	Standard
Engine and Compartment Lighting	Standard
Driver Delivery Seat	Standard
ISRI 6832 3 pt seat belt air ride seat	Optional
ISRI 6832 climate control (heater and air circulation)	Optional
Exterior Graphic Design Assistance	Optional
Factory Exterior Paint w/Special Effects	Optional
Back-up Sound Alarm	Standard
Headlamp Cleaning System	Standard
Glossy Black Wood & Leather Smart Steering Wheel	Standard